

TRAVELER OXIMETER

A new generation of Traveler Pulse Oximeter is specially designed to be used by healthcare and emergency rescue professionals for quickly spot check on oxygen saturation and pulse rate through non invasive measuring.

Traveler Oximeter is developed by new integrate technology of IR applications. It provides a wide range of measurement, low power consumptions, simple operation, fast response and high level accuracy on a light-weight design unit for easy had carry that gives you an observation of oxygen status at everywhere to fit as your needs between first aid and individual.

A large LED display clearly indicates numerical readings and pulse rate strength in real time. Plus all in one functionally together with unique, sharpness, compact, mechanism designed.













MD 650P SPECIFICATION

SPECIFICATIONS

SpO₂

Range: 0% ~ 100%

70% ~ 100% ± 2% SpO₂ Accuracy:

50% ~ 69% ± 3%

< 50% unspecified

Pluse Rate Range: 20 ~ 250 bpm

Pulse Accuracy: $20 \sim 250 \text{ bpm} \pm 1\%$

Probe type: Built-in Adult Finger Probe

Temperature: $0 \sim 55\%$ (Operating)

 $-20 \sim 70\%$ (Storage)

Humidity: $15 \sim 95\%$ (Operating)

 $10 \sim 95\%$ (Storage)

Power Requirement: 3 pcs AAA Size battery

Quick measurement: 8 seconds depend on pulse rate

Power Management: Power saving function, 10 seconds

auto power off when not measuring

Mechanical Design: All in one, finger type

Dimensions: 73(L) x 45(W) x 39(H) mm

Weight: 60 g (Net)

ISO 9001, ISO 13485, GMP Quality System:

FDA (E 0434

EN-60601-1, EN60601-1-1, Safety:

COMDEK INDUSTRIAL CORP.

7F, No. 1, Alley 6, Lane 235, Pao-Chiao Rd., Hsin-Tien Dist., New Taipei City 23145, Taiwan Tel: 886-2-2918-1266 Fax: 886-2-2918-1277

http://www.comdek.com

Email: medical@comdek.com

EN-60601-1-2

FEATURES

- * Any patient from pediatric to adult
- * Compact and modern design
- * All in one with built-in finger probe
- * Quick response of SpO₂ & Pulse Rate
- * Easy carry for spot-checking
- * Pulse strength by full scale light bar indicator
- * Large and Light LED indicator
- * Easy to read for any time and any where
- * Uses "AAA" battery
- * Battery life approx. 30 hours continuous use
- * Low battery indication (1 hour remains)
- * Low power consumption
- * Auto power off when not measuring

ACCESSORY

- 3 pcs AAA size alkaline batteries
- 2. Lanyard
- 3. Owner's manual

COLOR OPTIONAL



Order No. MD-650P-DB



Order No. MD-650P-LB



Order No. MD-650P-LY



Order No. MD-650P-LG

DISTRIBUTED BY:

^{*} Minimum order will be required.

^{*} Specifications are subject to change without notice